

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF

A PORTION OF THE NORTH, SOUTH AND EAST BOUNDARIES

AND

A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SUBDIVISION OF SECTIONS 3, 10, 15, 21, 22, 25, 27, 34 AND 36

IN

TOWNSHIP 28 SOUTH, RANGE 3 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under Special Instructions dated *January 8, 1999* and approve *January 8, 1999*, which provided for the surveys included under Group Number 895, and Assignment Instructions dated *January 15, 1999*.

Survey commenced January 26, 1999

Survey completed January 24, 2000

INDEX DIAGRAM

Township 28 South, Range 3 West

				4		2		
6	5	4	43	3	20	2		1
				42		31		
7	8	9		10	18	11		12
				41		29		
18	17	16	40	15	17	14		13
				46		39		28
19	20	45	21	37	22	15	23	24
				43		36		27
30	29	28	35	27	13	26	25	25
				34		24		23
31	32	33	32	34	12	35	22	36
				7		6		5

The Subdivisional Survey of Section 3.....	Page 47
The Subdivisional Survey of Section 10.....	Page 51
The Subdivisional Survey of Section 15.....	Page 53
The Subdivisional Survey of Section 21.....	Page 56
The Subdivisional Survey of Section 22.....	Page 61
The Subdivisional Survey of Section 25.....	Page 63
The Subdivisional Survey of Section 27.....	Page 64
The Subdivisional Survey of Section 34.....	Page 68
The Subdivisional Survey of Section 36.....	Page 70

TOWNSHIP 28 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the north, south and east boundaries, a portion of the subdivisional lines, and the subdivision of secs. 3, 10, 15, 21, 22, 25, 27, 34 and 36, in Township 28 South, Range 3 West, Salt Lake Meridian, Utah.

History of Earlier Surveys

Surveyed by

Retr. or Resurveyed by

NORTH BOUNDARY

Portion	J. Gorlinski	1871		
Portion	Breckon	1896		
Portion			G.E. Reynolds	1989

SOUTH BOUNDARY

Portion	J. Gorlinski	1871
Portion	Breckon and McCarty	1897

EAST BOUNDARY

All	Breckon and McCarty	1897
-----	---------------------	------

WEST BOUNDARY

Portion	J. Gorlinski	1871		
Portion	Breckon and McCarty	1897	Breckon and McCarty	1897
Portion			Page and Erwin	1900
Portion			G.E. Reynolds	1989

SUBDIVISION

Portion	J. Gorlinski	1871		
Portion	Breckon and McCarty	1897	Breckon and McCarty	1897
Portion			G.E. Reynolds	1989
Remonumentation			F.D. Reynolds	1972

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instruction, 1973, and the Special Instructions for Group No. 895, Utah, dated January 8, 1999.

The direction of lines were determined by references to true meridians established on line by hour angle observations of the Sun. The lines were carried forward by sustained angulation. Distances were determined in feet by electronic measurement. Global Positioning System (GPS) utilizing relative positioning techniques was also utilized during the course of the

TOWNSHIP 28 SOUTH, RANGE 3 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

survey. Geodetic bearings were determined by inverse between cors. Cadastral Measurement Management (CMM) was also utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the cor. of Tps. 28 and 29 S., Rs. 2 1/2 and 3 W., as determined by a tie made to the National Geodetic Survey triangulation station "LAKE", utilizing GPS, utilizing relative positioning techniques, is as follows:

Latitude 38° 19' 32.493" N. Longitude: 112° 08' 29.178" W.
N.A.D. 1983(1994)

This cor. will now function as a BLM control station.

The geographic position of tri-station "LAKE " is as follows:

Latitude 38° 20' 26.73814" N. Longitude: 112° 12' 37.91573" W.
N.A.D. 1983(1994) Elevation 6252 ft.

The mean magnetic declination as determined from the U.S. Geological Survey Magnetic Declination Map of 1990, is: 14 1/2°E.

Dependent Resurvey of a Portion of the North Boundary
T. 28 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J.T. Breckon in 1896

Beginning at the 1/4 sec. cor. of sec. 35 only, on the south bdy. of T. 27 S., R. 3 W., monumented with a lava stone, 14X6X9 ins., firmly set, clearly mkd. with a 4 on north face, with a reference mound of stone, 2 1/2 ft. diam., North, 5 lks. dist. (Record; 18X16X12 ins., mkd. 1/4 on north face)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T27S R3W
1/4 S35

T28S
1999

Bury mkd. stone along south side of aluminum post.

Rebuild reference mound of stone to 4 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a slight NW slope in sagebrush.

S. 89°50.1' W., on the south bdy. of sec. 35.

37.969

Point for the closing cor. of secs. 2 and 3, T. 28 S., R. 3 W., hereinafter described.

40.037

The cor. of secs. 34 and 35 only, on the south bdy. of T. 27 S., R. 3 W., monumented with a sandstone, 18X14X8 ins., firmly set, mkd. with 2 notches on the west and 2 notches on the east edges, with a reference mound of stone to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T27S R3W
|
S34 | S35
—|—
S3
T28S R3W
1999

Bury mkd. stone along south side of aluminum post.

Rebuild reference mound of stone to 2 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual NE slope in sagebrush and 380 lks. West of a dirt road, 12 ft. wide, bears SE and NW.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.778

S. 88°04.7' W., on the south bdy. of sec. 34.

The 1/4 sec. cor. of secs. 3 and 34, Tps. 27 and 28 S., R. 3 W., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. as described in the field notes of the 1989 resurvey record. (Record; mound of stone, 3 ft. base, 2 ft. high, N of cor.)

Drive a steel fence post alongside stainless steel post.

Reestablishment of the Survey Executed by J. Gorkinski in 1871
and the Resurvey Executed by G.E. Reynolds in 1989

20.112

S. 89°31.3' W., bet. secs. 3 and 34, beginning new measurement.

Point for the W 1/16 sec. cor. of secs. 3 and 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with a magnet at base, and in a collar of stone, 2 ft. diam., with aluminum cap mkd.:

S34
W 1/16 —————
S3
1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual SW slope in sagebrush, and 90 lks. East of a dirt road, 8 ft. wide, bear N and S.

40.224

The cor. of secs. 3, 4, 33 and 34, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.

Cor. is located in meadow land, 54 lks. S of E and W barb wire fence line.

Dependent Resurvey of a Portion of the South Boundary
T. 28 S., R. 3 W., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH


CHAINS

Reestablishment of the Survey Executed by Breckon and McCarty in 1897

From the cor. of Tps. 28 and 29 S., Rs. 2 1/2 and 3 W., monumented with a sandstone, 20X14X10 ins., firmly set, clearly mkd. 28 S on northeast edge, 2 1/2 W on southeast edge, with the marks 29S on southwest edge and 3W on northwest edge, 6 notches on each edge, with a reference mound of stone to the southwest. (Record; reference mound of stone to the south)

At the cor. point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:



Bury mkd. stone on east side of stainless steel post.

Rebuild reference mound of stone to 3 ft. diam., around stainless steel post.

Cor. is located at the intersection of fences, bearing S and W, 50 lks. South of a draw, 10 lks. wide, drains NW.

S. 89°53.3' W., bet. secs. 1 and 36.

40.033

Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

80.066

T28S R3W
S36
1/4 —————
S1
T29S R3W
1999

Cor. is located on a flat in sagebrush and the westerly edge of scattered juniper, in a fence, bears E and W.

The cor. of secs. 1, 2, 35 and 36, monumented with an iron stone, 18X14X7 ins., firmly set, with 5 notches on the west and 1 notch on the east edges, with a reference mound of stone, 3 ft. diam., to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
|
S35|S36
—|—
S2|S1
|
T29S R3W
1999

Bury mkd. stone on north side of aluminum post.

Cor. is located in sagebrush, in a fence, bears E-W, and 50 lks. East of a draw, drains NE.

39.784

N. 89°57.3' W., bet. secs. 2 and 35.

The 1/4 sec. cor. of secs. 2 and 35, monumented with a lave rock, 18X14X7 ins., firmly set, clearly mkd. 1/4 on north, with a reference mound of stone, 3 ft. diam., to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W
S35
1/4 —————
S2
T29S R3W
1999

Cor. is located in sagebrush, and in a fence, bears E and W, 50 lks. West of a wire gate.

N. 89°35.6' W., beginning new measurement.

44.869

Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T28S R3W
|
S34 S35
— S3 S2 —
|
T29S
1999

Cor. is located on a westerly slope in scattered juniper and sagebrush, 40 lks. East of a draw, drains NW, 75 lks. North of a fence, bears NE and SW, 75 lks. West of westerly edge of boulders.

Reestablishment of the Survey Executed by J. Gorlinski in 1871

N. 89°35.6' W., bet. secs. 3 and 34.

20.166

Point for the E 1/16 sec. cor. of secs. 3 and 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH


CHAINS	
40.332	<div style="text-align: center;"> <p>S34 E1/16 ————— S3 1999</p> </div> <p>Cor. is located on a steep northerly slope in sagebrush, 120 lks. North of a fence, bears NE and SW.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 3, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with brass cap mkd.:</p>
60.498	<div style="text-align: center;"> <p>T28S R3W S34 1/4 ————— S3 T29S 1999</p> </div> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a gradual west slope in scattered sagebrush, 10 lks. West of a dirt road, 8 ft. wide, bears NE and SW.</p> <p>Point for the W 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with brass cap mkd.:</p>
80.664	<div style="text-align: center;"> <p>S34 W 1/16 ————— S3 1999</p> </div> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a small spur ridge, bears NE and SW.</p> <p>The cor. of secs. 3, 4, 33 and 34, monumented with a red sandstone, 16X12X14 ins., loosely set, mkd. with 3 notches on the west, in a mound of stone, 3 ft. diam. (Record; no marks on red sandstone, no mound of stone)</p>

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone along westside of aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on an easterly slope in sagebrush, 121 lks. North of a spur ridge, bears SE and NW.


Dependent Resurvey of a Portion of the East Boundary
T. 28 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by Breckon and McCarty in 1897

From the 1/4 sec. cor. of secs. 32 and 36, monumented with a trachyte, 14X13X5 ins., loosely set, clearly mkd. 1/4 on west face, with a reference mound of stone to the west.

At the cor. point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., with brass cap mkd.:



Bury mkd. stone on northside of stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Rebuild reference mound of stone to a collar of stone.

Cor. is located on a flat in scattered sagebrush.

N. 0°06.5' W., bet. secs. 32 and 36.

20.050


Point for the N 1/16 sec. cor. of secs. 32 and 36. Not monumented.

40.100

The cor. of secs. 25, 29, 32 and 36, monumented with a trachyte, 14X8X6 ins., loosely set, dimly mkd. with 5 grooves on the north and one groove on the south sides, with a reference mound of stone to the west (Record; 5 notches on the north and 1 notch on the south edges)

At the cor. point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with a magnet at base, and in a collar of stone, 2 ft. diam., with brass cap mkd.:



Bury mkd. stone on southside of stainless steel post.

Rebuild reference mound of stone to collar of stone around stainless steel post.

Drive a steel fence post alongside stainless steel post.

Cor. is located on a flat in sagebrush.

N. 0°15.0' E., bet. secs. 25 and 29.

40.149

The 1/4 sec. cor. of secs. 25 and 29, monumented with a trachyte, 14X8X8 ins., loosely set, clearly mkd. 1/4 on west face, in a mound of stone, 3 ft. diam. (Record; reference mound of stone to the west)

At the cor. point

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T28S
R3W R 2 1/2W
1/4
S25 | S29
1999

Bury mkd. stone on northside of aluminum post.

Rebuild reference mound of stone to mound of stone around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a flat in sagebrush.

N. 0°19.4' W., beginning new measurement.

39.855

The cor. of secs. 20, 24, 25 and 29, monumented with a trachyte, 16X18X10 ins., loosely set, mkd. with 4 notches on the north and 2 notches on the south edges, with a reference mound of stone to the west.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S
R3W R2 1/2W
S24 | S20
S25 | S29
1999

Bury mkd. stone along westside of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located 250 lks. East of a dirt road, 7 ft. wide, bears SE and NW.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 28 S., R. 3 W., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by J. Gorkinski in 1871 and the
Resurvey Executed by Breckon and McCarty in 1897

From the cor. of secs. 2, 3, 34 and 35, on the south bdy. of the tp., hereinbefore described.

N. 1°10.9' E., along the east bdy. of sec. 34.

39.817

Point for the 1/4 sec. cor. of sec. 35 only, at midpoint bet. the cor. of secs. 2, 3, 34 and 35 and the original closing cor. of secs. 26 and 35, and on the east bdy. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.:

T28S R3W

1/4
S35

1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a southerly slope in sagebrush.

41.135

Point for the 1/4 sec. cor. of sec. 34 only, at proportionate dist., there is no remaining evidence of the original cor. Note: This cor. was not monumented during the resurvey by Brecken and McCarty in 1897.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., with brass cap mkd.:

T28S R3W

1/4
S34

1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Drive a steel fence post alongside stainless steel post.

Cor. is located on a west slope in sagebrush.

79.634


Point for the closing cor. of secs. 26 and 35, hereinafter described.

82.270

The cor. of secs. 27 and 34 only, monumented with a granite rock, 18X14X10 ins., loosely set, mkd. with 1 groove on the south and 2 grooves on the east edges, with a reference mound of stone to the east. (Record; no reference mound)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone on westside of aluminum post.

Drive a steel fence post alongside aluminum post.


Cor. is located on a west slope in sagebrush.

N. 0°50.7' W., along the east bdy. of sec. 27.

19.329

Point for the S 1/16 sec. cor. of sec. 27 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:



1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH


CHAINS	
36.862	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on top of a ridge, bears NE and SW.</p> <p>Point for the 1/4 cor. of sec. 26 only, at midpoint between closing cors. and on the east bdy. of sec. 27.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>T28S R3W</p> <p>1/4</p> <p>S26</p> <p>1999</p> </div>
38.658	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a flat in sagebrush.</p> <p>Point for the 1/4 sec. cor. of sec. 27 only, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T28S R3W</p> <p>1/4</p> <p>S27</p> <p>1999</p> </div>
57.987	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a flat in sagebrush.</p> <p>Point for the N 1/16 sec. cor. of sec. 27 only. Not monumented.</p>
76.360	<p>Point for the closing cor. of secs. 23 and 26, hereinafter described.</p>
77.316	<p>The cor. of secs. 22 and 27 only, monumented with a red sandstone, 14X8X8 ins., loosely set, mkd. with 2 grooves on the south and 2 grooves on the east edges, with a reference mound of stone to the south.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone to the south of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.


Cor. is located on a flat in sagebrush and in a fence, bears N and S.

N. 0°52.2' W., along the east bdy. of. sec. 22.

39.499

Point for the 1/4 sec. cor. of sec. 23 only, at midpoint between closing cors. and on the east bdy. of sec. 22.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:



Drive a steel fence post alongside stainless steel post.

Cor. is located on a gradual south slope in rabbit brush, and 15 lks. North of a wash, 8 ft. wide, drains southwest.

40.892

Point for the 1/4 sec. cor. of sec. 22 only, at proportionate dist., utilizing irregular bdy. adjustment, there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T28S R3W

1/4
S22

1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a northeast slope in rabbit brush.

N. 0°47.2' W., beginning new measurement.

20.426

Point for the N 1/16 sec. cor. of sec. 22 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 1/2 ft. diam., to top, with aluminum cap mkd.

N 1/16
S22

1999

Cor. is located 5 lks. West of a draw, drains NW, and 8 lks. South of same draw, drains NW.

39.062

Point for the closing cor. of secs. 14 and 23, hereinafter described.

40.852


The cor. of secs. 15 and 22 only, monumented with a conglomerate rock, 16X9X8 ins., loosely set, in a mound of stone, 3 ft. diam. (Record; no mound of stone)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS



Bury conglomerate rock north of aluminum post.

Rebuild mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.


Cor. is located on a gradual south slope in sagebrush.

N. $0^{\circ}16.3'$ W., along the east bdy. of sec. 15.

38.343

Point for the 1/4 sec. cor. of sec. 14 only, at midpoint bet. original closing cors. and on the east bdy. of sec. 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 17 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside aluminum post.

Cor. is located on a rocky southerly slope in sagebrush.

40.326

The 1/4 sec. cor. of sec. 15 only, monumented with a granite rock, 18X16X12 ins., loosely set, in a mound of stone, 2 1/2 ft. diam. (Record; no mound of stone)

At the cor. point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:

T28S R3W

1/4
S15

1999

Bury original granite rock on north side of aluminum post.

Rebuild original mound of stone to 4 ft. diam. around aluminum post.

Cor. is located on a south slope in sagebrush.

N. 0°17.0' W., beginning new measurement.

38.150

Point for the closing cor. of secs. 11 and 14, hereinafter described.

40.329

The cor. of secs. 10 and 15 only, monumented with an aluminum post, firmly set, projecting 20 ins. above ground, in a mound of stone, with aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.

Cor. is located on a westerly slope in scattered sagebrush.

N. 2°55.0' W., along the east bdy. of sec. 10.

37.519

Point for the 1/4 sec. cor. of sec. 11 only, at midpoint bet. original closing cors. and on the east bdy. of sec. 10.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with aluminum cap mkd.:

T28S R3W

1/4
S11

1999

Drive a steel fence post alongside aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

39.490

Cor. is located on a southeast slope in sagebrush and grass.

The 1/4 sec. cor. of sec. 10 only, monumented with an embedded mound of stone, 2 ft. diam. (Record; quartzite rock, 16X12X9 ins., no mound of stone). This mound of stone is accepted as the best available evidence and a careful and faithful determination of the original corner position.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W

1/4

S10

1999

Rebuild original mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a southeast slope in sagebrush and grass.

20.159

N. 0°16.6' W., beginning new measurement.

Point for the N 1/16 sec. cor. of sec. 10 only.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with aluminum cap mkd.:

N 1/16

S10

1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a spur ridge on a gradual westerly slope in sagebrush.

37.675

Point for the closing cor. of secs. 2 and 11, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.318

True point for the cor. of secs. 3 and 10 only, at proportionate dist., utilizing irregular bdy. adjustment, there is no remaining evidence of the original cor., falls on a nearly vertical road cutbank, where it is unsuitable for monumentation.

True cor. point is located 40 lks. North of an improved dirt road, 20 ft. wide, bears E and W.


Reestablishment of the Survey Executed by Breckon and McCarty in 1897

N. 0°29.3' E., along the east bdy. of sec. 3.

0.204

Point selected for the witness cor. for the cor. of secs. 3 and 10 only.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:




Drive a steel fence post alongside stainless steel post.

37.552

Point for the 1/4 sec. cor. of sec. 2 only, at proportionate dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:



Drive a steel fence post alongside stainless steel post.

Cor. is located on a spur ridge on a southerly slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.130

Point for the 1/4 sec. cor. of sec. 3 only, at proportionate dist., there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T28S R3W

1/4	
S3	

1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a spur ridge, on a gradual southerly slope in sagebrush.

80.340

Point for the closing cor. of secs. 2 and 3, T. 28 S., R. 3 W., at intersection with the south bdy. of sec. 35, T. 27 S., R. 3 W.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with brass cap mkd.

T27S R3W

S35	
S3	S2
C	C
T28S	R3W

1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a gradual SE slope in sagebrush.

From this point the original closing cor. of secs. 2 and 3, bears N. 0° 29.3' E., 0.021 chs. dist., monumented with a trachyte, 20X4X8 ins., loosely set, dimly mkd. with 2 grooves on the east and 4 grooves on the west faces, with a reference mound of stone to the south. I add the marks AM and bury the stone 6 ins. below the surface of the ground. Use stones from reference mound for a collar of stone around stainless steel post for the closing cor.

From the cor. of secs. 1, 2, 35 and 36, on the south bdy. of the tp., hereinbefore described.


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
20.053	<p>N. 0°04.3' W., bet. secs. 35 and 36.</p> <p>Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">S1/16 S35 S36 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a westerly slope in sagebrush and 200 lks. East of a draw, drains northwest.</p>
40.106	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a lava stone, 18X14X10 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone, 3 ft. diam.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">T28S R3W 1/4 S35 S36 1999</p> <p>Bury mkd. stone on north side of stainless steel post.</p> <p>Rebuild mound of stone to 3 ft. diam. around stainless steel post.</p> <p>Cor. is located on an easterly slope in sagebrush and 100 lks. West of a draw, drains southwest.</p>
39.994	<p>N. 0°01.6' W., beginning new measurement.</p> <p>The cor. of secs. 25, 26, 35 and 36, monumented with a lava stone, 36X8X8 ins., firmly set, mkd. with 1 notch on the east and 1 notch on the south edges, in a mound of stone, 4 ft. diam. (Record; mound of stone to the west)</p> <p>At the cor. point</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:



Bury mkd. stone east of aluminum post.

Rebuild original mound of stone to 5 ft. diam. around aluminum post.

Cor. is located on a steep and rocky southwest slope,


From the cor. of secs. 25, 29, 32 and 36, on the east bdy. of the tp., hereinbefore described.

S. 89°51.5' W., bet. secs. 25 and 36.

19.985

Point for the E 1/6 sec. cor. of secs. 25 and 36.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, with brass cap mkd.:



Drive a steel fence post alongside stainless steel post.

Cor. is located on a flat in sagebrush.

39.970

The 1/4 sec. cor. of secs. 25 and 36, monumented with a trachyte, 12X8X8 ins., loosely set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W
S25
1/4 —————
S36
1999

Bury mkd. stone south of aluminum post.

Rebuild reference mound of stone to 2 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a flat area in sagebrush.

S. 89°50.7' W., beginning new measurement.

40.027

The cor. of secs. 25, 26, 35 and 36.

S. 89°56.9' W., bet. secs. 26 and 35.

39.950

The 1/4 sec. cor. of secs. 26 and 35, monumented with a lava stone, 12X8X6 ins., firmly set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
S26
1/4 —————
S35
1999

Bury mkd. stone along west side of aluminum post.

Rebuild reference mound to a 3 ft. mound around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a spur ridge, bears NE and SW, and in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

42.905

S. 89°52.2' W., beginning new measurement.

The original closing cor. of secs. 26 and 35, monumented with a lave stone, 14X9X7 ins., firmly set, clearly mkd. with CC on east face, and 2 grooves on the north and 1 groove on the south edges, with a reference mound of stone, 2 ft. diam., to the east.


I add the marks AM and bury the stone 6 ins. below the surface of the ground.

The stones from the reference mound were used to build a mound of stone for the closing cor. of secs. 26 and 35.

42.973

Point for the closing cor. of secs. 26 and 35, at intersection with the east bdy. of sec. 34.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside aluminum post.

Cor. is located on a west slope in sagebrush.

39.566

From the cor. of secs. 25, 26, 35 and 36.

N. 0°01.9' W, bet. secs. 25 and 26

The 1/4 sec. cor. of secs. 25 and 26, monumented with a trachyte, 12X8X6 ins., firmly set, clearly mkd. 1/4 on west face, with a reference mound of stone to the west.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W

1/4

S26 | S25

1999

Bury mkd. stone on north side of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a southerly slope in sagebrush.

N. 0°10.0' W., beginning new measurement.

40.418

The cor. of secs. 23, 24, 25 and 26, monumented with a trachyte, 12X9X7 ins., firmly set, clearly mkd. with 2 notches on the south and 1 notch on the east edges, with a reference mound of stone to the north.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.

T28S R3W

S23	S24
S26	S25

1999

Bury mkd. stone along north side of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a westerly slope in scattered sagebrush, and 50 lks. East of a draw, drains northwest.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
40.043	<p>From the cor. of secs. 20, 24, 25 and 29, on the east bdy. of the tp., hereinbefore described.</p> <p>S. 89°58.7' W., bet. secs. 24 and 25.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with a trachyte, 15X8X5 ins., firmly set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.</p> <p>At the cor. point</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, with brass cap mkd.:</p> <div style="text-align: center;"> <p>T28S R3W</p> <p>S24</p> <p>1/4 —————</p> <p>S25</p> <p>1999</p> </div> <p>Bury mkd. stone on northside of stainless steel post.</p> <p>Rebuild reference mound of stone to 3 ft. diam. around stainless steel post.</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in sagebrush, 125 lks. North of a fence, bears E and W.</p> <p>_____</p> <p>S. 89°41.7' W., beginning new measurement.</p>
40.030	<p>The cor. of secs. 23, 24, 25 and 26.</p>
39.984	<p>S. 89°53.4' W., bet. secs. 23 and 26.</p> <p>The 1/4 sec. cor. of secs. 23 and 26, monumented with a trachyte, 16X12X6 ins. firmly set, with no marks visible, with a reference mound of stone to the north. (Record; 12X10X9 ins., mkd. 1/4 on north)</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W
S23
1/4 —————
S26
1999

Bury original stone on north side of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a spur ridge, bears N and S, and in scattered sagebrush.

S. 88°37.7' W., beginning new measurement.

43.867

Point for the closing cor. of secs. 23 and 26, at intersection with the east bdy. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
|
S23 C
S27 ——— S26 C
|
1999

Cor. is located on a flat in sagebrush and 5 lks. West of a fence, bears N and S.

From this point the original closing cor. of secs. 23 and 26, bears S. 88° 37.7' W., 3.375 chs. dist., monumented with a red sandstone, 16X12X5 ins., firmly set, clearly mkd. CC on east face, with a reference mound of stone to the east, (Record; trachyte, 2 grooves on south and east faces). Add the marks AM to the mkd. stone and bury in place 4 ins. below ground. Scatter reference mound of stone.

NOTE: This cor. is to be used for sec. Line alignment only. The lottings in secs. 23 and 26, will not utilize this corner but be proportioned from the new closing corner position on the east bdy. of sec. 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 sec. cor. of secs. 14 and 23, monumented with a lava stone, 13X8X5 ins., firmly set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north. (Record; iron stone, 15X10X6 ins.)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
S14
1/4 —————
S23
1999

Bury mkd. stone south of aluminum post.

Rebuild reference mound to 3 ft. diam. around aluminum post.

Cor. is located on a southwesterly slope in sagebrush.

S. 89°56.4' W., bet. secs. 14 and 23.

45.293

Point for the closing cor. of secs. 14 and 23, at intersection with the east bdy. of sec. 27.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.

T28S R3W
|
S14 C
S22 ——— S23 C
|
1999

From this point the original closing cor. of secs. 14 and 23, bears S. 89° 56.4' W., 0.052 chs. dist., monumented with a lava stone, 14X8X5 ins., loosely set, clearly mkd. with 3 grooves on the south and 2 grooves on the east edges, and CC on the east face, with a reference mound of stone to the east. Add the marks AM to the mkd. stone and use it as part of the mound of stone around the aluminum post.

Cor. is located on a gradual and rocky southerly slope in sagebrush.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH


CHAINS

From the cor. of secs. 11, 12, 13 and 14, monumented with an embedded mound of stone, 4 ft. diam. (Record; trachyte, 16X12X10 ins., mkd. with 4 notches on the south and 1 notch on the east edges). No remaining evidence of the bearing trees were recovered.

This mound of stone is accepted as the best available evidence and a careful and faithful determination of the original corner position.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with aluminum cap mkd.:



Rebuild original mound of stone to 5 ft. diam. around aluminum post.


Cor. is located on a south slope in sagebrush.

S. 89°05.2' W., bet. secs. 11 and 14.

39.730

Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside aluminum post.

Cor. is located on a flat in a chained and seeded area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

59.595

Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

S11
W 1/16 ———
S14
1999

Cor. is located on a flat in grass and 200 lks. East of a fence, bears N and S.

85.631

Point for the closing cor. of secs. 11 and 14, at intersection with the east bdy. of sec. 15.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
|
S15 | S11 C
| S14 C
|
1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a west slope in sagebrush.

From this point the original closing cor. of secs. 11 and 14, bears S. 89° 05.2' W., 0.037 chs. dist., monumented with a lava stone, 15X10X8 ins., loosely set, clearly mkd. with 4 grooves on the south edge and CC on the east face. Add the marks AM to mkd. stone and bury 6 ins. below ground.

From the 1/4 sec. cor. of secs. 2 and 11, monumented with a lave stone, 11X8X8 ins., firmly set, with no marks visible, with a reference mound of stone to the north. (Record; trachyte, 10X8X8 ins., mkd. 1/4 on north face)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W
S2
1/4 —————
S11
1999

Bury mkd. stone on east side of aluminum post.

Rebuild reference mound of stone to 3 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a slight northwest slope in sagebrush, 10.6 chs. South of an unimproved dirt road, 7 ft. wide, bears E and W.

S. 89°49.3' W., bet. secs. 2 and 11.

46.706

Point for the closing cor. of secs. 2 and 11, at intersection with the east bdy. of sec. 10.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T28S R3W
|
S2 C
S10 ——— S11 C
|
1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a north slope in sagebrush, and 250 lks. South of a dirt road, 20 ft. wide, bears E and W.

From this point the original closing cor. of secs. 2 and 11, bears S. 89° 49.3' W., 0.356 chs. dist., monumented with a trachyte, 20X14X18 ins., loosely set, clearly mkd. with 5 grooves on the south and 2 grooves on the north edges, and CC on the east face, with a reference mound of stone to the east Add the marks AM to mkd. stone and bury 6 ins. below ground. The stones from the reference mound were used to build a mound of stone, 3 ft. diam., around the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by J. Gorkinski in 1871

37.781

From the cor. of secs. 3, 4, 33 and 34, on the south bdy. of the tp., hereinbefore described.

N. 0°56.5' E., bet. secs. 33 and 34.

The 1/4 sec. cor. of secs. 33 and 34, monumented with a white flintstone, 18X16X12 ins., loosely set, dimly mkd. 1/4 on west face, in a collar of stone. (Record; white flintstone not mkd., no collar of stone)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., with aluminum cap mkd.:

T28S R3W

1/4

S33 | S34

1999

Bury mkd. stone on south side of aluminum post.

Rebuild collar of stone to 1 1/2 ft. diam. around aluminum post.

Cor. is located on a gradual NW slope in sagebrush.

40.118

N. 0°35.4' W., beginning new measurement.


The cor. of secs. 27, 28, 33 and 34, monumented with an iron stone, 20X13X18 ins. diam., firmly set, mkd. with 3 notches on the south and 3 notches on the east edges. (Record; no notches)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS



1999

Bury mkd. stone northwest of aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual easterly slope, 15 lks. North of a dirt road, 8 ft. wide, bears E and W.

From the cor. of secs. 27 and 34 only.

S. 87°21.6' W., bet. secs. 27 and 34.

20.555

The E 1/16 sec. cor. of secs. 27 and 34, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a faithful and careful determination of the position of the cor.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, with brass cap mkd.:

S27
E 1/16 —————
S34
1999

Bury rebar inside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a slight northeasterly slope in scattered sagebrush.

S. 87°21.6' W., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

20.555

The 1/4 sec. cor. of secs. 27 and 34, monumented with an unrecorded rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a faithful and careful establishment of the position of the cor.

At the cor. point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with brass cap mkd.:

T28S R3W
S27
1/4 —————
S34
1999

Bury rebar inside stainless steel post.

Drive a steel fence post alongside stainless steel post.

Cor. is located on a steep north slope, 30 lks. South of a draw, drains SE.

—————
S. 87°21.6' W., beginning new measurement.

41.111

The cor. of secs. 27, 28, 33 and 34.

—————
N. 0°27.7' W., bet. secs. 27 and 28.

40.308

The 1/4 sec. cor. of secs. 27 and 28, monumented with a granite stone, 20X15X15 ins., loosely set, dimly mkd. 1/4 on west face.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a magnet at base, with aluminum cap mkd.:

T28S R3W
1/4
S28 | S27
1999

Bury mkd. stone along north side of aluminum post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.403

Drive a steel fence post alongside aluminum post.


Cor. is located in sagebrush, and 450 lks. West of a dirt road, 8 ft. wide, bears N and S.

N. $0^{\circ}39.8'$ W., beginning new measurement.

The cor. of secs. 21, 22, 27 and 28, monumented with a white sandstone, 10X10X10 ins., no mks. visible, loosely set, in a collar of stone. (Record; no collar of stone)

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:



Bury white sandstone on west side of aluminum post.

Rebuild collar of stone to 1 ft. diam. around aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located in sagebrush, and 110 lks. North of a dirt road, 12 ft. wide, bears NE and SW.

20.443

From the cor. of secs. 22 and 27 only.

S. $89^{\circ}43.7'$ W., bet. secs. 22 and 27.

Point for the E 1/16 sec. cor. of secs. 22 and 27. Not monumented.

40.886

The 1/4 sec. cor. of secs. 22 and 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, 2 ins. below ground, and is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a steel fence post, 60 ins. long, 54 ins. in the ground and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with a magnet at base over steel fence post, with aluminum cap mkd.:

T28S R3W
S22
1/4 —————
S27
1999

Bury rebar inside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on the flood plain of the Sevier River, 212 lks. East of the Sevier River, 100 ft. wide, flows northeast.

—————
S. 89°43.7' W., beginning new measurement.

20.443

The W 1/16 sec. cor. of secs. 22 and 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a careful and faithful determination of the position of the cor.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:

S22
W 1/16 —————
S27
1999

Bury rebar along west side of aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual south slope in sagebrush.

—————
S. 89°43.7' W., beginning new measurement.

20.443

The cor. of secs. 21, 22, 27 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
20.204	<p>N. 0°45.2' W., bet. secs. 21 and 22.</p> <p>The S 1/16 sec. cor. of secs. 21 and 22, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>S1/16 S21 S22 1999</p> </div> <p>Bury rebar inside aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a flat in sagebrush.</p> <hr/>
20.204	<p>N. 0°45.2' W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with an aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located on a flat in scattered sagebrush.</p> <hr/>
20.015	<p>N. 1°55.0' E., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>N 1/16 S21 S22 1999</p> </div>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS


40.030

Drive a steel fence post alongside aluminum post.

Cor. is located on a tri-angle shaped road berm, 60 lks. North of the south end of road junctions.

Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



Drive a steel fence post alongside aluminum post.

From this point a recorded rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, with yellow plastic cap mkd. R.W. FRIANT L.S. 154652, record #43 (surveyed for Paul Swalberg in 1999), Piute County Records office, bears S. 89°21.9' W., 1.093 chs. dist., was set using incorrect procedures and was not utilized during the course of this resurvey.

Cor. is located on a gradual northeasterly slope in a pasture, and 30 lks. North of center of power line, bears E and W.


19.246

From the cor. of secs. 15 and 22 only, hereinbefore described.

S. 88° 45.4' W., bet. secs. 15 and 22.

Point for the E 1/16 sec. cor. of secs. 15 and 22.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:



DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a northerly slope in scattered sagebrush, and 30 lks. South of a draw, drains northeasterly.</p>
38.492	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a sandstone, 14X12X12 ins., firmly set, clearly mkd. 1/4 on north face. (Record; lava rock, 14X8X8 ins.)</p> <p>At the cor. point</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground to bedrock, with a magnet at base, with brass cap mkd.:</p> <div style="text-align: center;"> <p>T28S R3 W</p> <p>S15</p> <p>1/4 —————</p> <p>S22</p> <p>1999</p> </div>
	<p>Bury mkd. stone on north side of stainless steel post.</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located in grass and pasture, and 4 lks. South of a fence, bears E and W.</p>
20.647	<p>S. 88°47.2' W., beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 15 and 22. Not monumented.</p>
41.294	<p>The cor. of secs. 15, 16, 21 and 22.</p>
20.010	<p>N. 1°21.0' W., bet. secs. 15 and 16.</p> <p>Point for the S 1/16 sec. cor. of secs. 15 and 16. Not monumented.</p>
40.020	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist., there is no remaining evidence of the original cor., falls in a tilled field where a monument would be subject to destruction. Not monumented.</p> <p>Note: Record #43 (survey for Paul Swalberg in 1999), Piute County Records office, indicates a rebar and plastic cap were set for the 1/4 sec. cor. of secs. 15 and 16. No evidence of the rebar and plastic cap were recovered.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
60.030	Point for the N 1/16 sec. cor. of secs 15 and 16. Not monumented.
80.040	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an aluminum post, firmly set, flush with ground. Note: The aluminum cap has been removed.</p> <p>Note: Subsequent to the recovery of the aluminum post, the aluminum post was removed. Because the cor. is in an alfalfa field and subject to destruction, the decision was made to set a reference monument.</p> <p>from which</p> <p>An aluminum post, 2 1/2 ins. diam., 30 ins. long, 23 ins. in the ground for a reference monument with a magnet at base, bears S. 62°57.8' W., 162.8 lks. dist., with aluminum cap mkd. RM T28S R3W S16 TO COR 1999 and an arrow pointing to the cor. Cor. is located on a gradual northeasterly slope, 100 lks. East of a dirt road, 14 ft. wide, bears NE and SW.</p>
	<hr/> <p>Reestablishment of the Survey Executed by J. Gorlinski in 1871 and the Resurvey Executed by G.E. Reynolds in 1989</p> <hr/>
	From the cor. of secs. 10 and 15 only.
	S. 88°21.2' W, bet. secs. 10 and 15.
40.643	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located on a south slope in sagebrush, and 90 lks. South of a fence, bears E and W.</p>
	S. 88°20.3' W., beginning new measurement.
20.318	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p>
	<p style="text-align: center;">S10 W 1/16 ————— S15 1999</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
40.636	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a gradual easterly slope in sagebrush and rabbit brush, and 150 lks. East of a fence, bears N and S.</p> <p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p>Reestablishment of the Survey Executed by J. Gorlinski in 1871 and the Retracement Executed by Breckon and McCarty in 1897</p> <hr/> <p>From the true point for the cor. of secs. 3 and 10 only.</p> <p>S. 88°22.6' W., bet. secs. 3 and 10.</p>
20.217	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>S3</p> <p>E 1/16 —————</p> <p>S10</p> <p>1999</p> </div>
40.434	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southerly slope, approximately 400 lks. North of a dirt road, 18 ft. wide, bears E and W.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist., utilizing irregular bdy. adjustment, there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>T28S R3W</p> <p>S3</p> <p>1/4 —————</p> <p>S10</p> <p>1999</p> </div>
	<p>Drive a steel fence post alongside aluminum post.</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Cor. is located on a flat in sagebrush.</p> <hr/> <p>S. 88°40.6' W., beginning new measurement.</p>
20.214	Point for the W 1/16 sec. cor. of secs. 3 and 10. Not monumented.
40.428	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located in 7 strand barbwire fence line and on northside of improved gravel road, bears E-W.</p> <hr/> <p>Reestablishment of the Survey Executed by J. Gorlinski in 1871, the Retracement Executed by Breckon and McCarty in 1897, and the Resurvey Executed by G.E. Reynolds in 1989</p> <hr/> <p>N. 0°16.6' W., bet. secs. 3 and 4.</p>
20.449	Point for the S 1/16 sec. cor. of secs. 3 and 4. Not monumented.
40.898	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with an aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located in netwire fence line, bears E and W, on a flat in grass and sagebrush.</p> <hr/> <p>Reestablishment of the Survey Executed by J. Gorlinski in 1871</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°31.2' W., bet. secs. 21 and 28.</p>
19.952	<p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 1/2 ft. diam., to top, with aluminum cap mkd.:</p>


DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
39.904	<div data-bbox="683 425 870 544"> $\begin{array}{c} \text{S21} \\ \text{E } 1/16 \text{ —————} \\ \text{S28} \\ 1999 \end{array}$ </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a slight east slope in sagebrush, and 30 lks. West of a draw, 2 ft. wide, drains NW.</p> <p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 10X8X8 ins., with no marks visible, with a reference mound of stone to the north. (Record; no reference mound)</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:</p> <div data-bbox="719 1002 870 1151"> $\begin{array}{c} \text{T28S R3W} \\ \text{S21} \\ 1/4 \text{ —————} \\ \text{S28} \\ 1999 \end{array}$ </div> <p>Bury sand stone along south side of aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located in a fence, bears N and S.</p> <hr/> <p>S. 87°46.1' W., beginning new measurement.</p>
20.265	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28, falls in an alfalfa field where it is subject to destruction. Not monumented.</p>
40.530	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a red sandstone, 15X10X8 ins., loosely set, mkd. with 2 grooves on the south face, in a mound of stone. (Record; limestone, no grooves called for)</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p>

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T28S R3W



Bury mkd. stone on north side of aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a flat in sagebrush.

N. 0°25.4' W., bet. secs. 20 and 21.

20.018

Point for the S 1/16 sec. cor. of secs. 20 and 21

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:

S 1/16
S20 | S21
1999

Drive a steel fence post alongside aluminum post.

Cor. is located on a gradual east slope, in sagebrush, 100 lks. West of a dirt road, 20 ft. wide, bears SE and NW.

40.036

The 1/4 sec. cor. of secs. 20 and 21, monumented with a granite sandstone, 12X8X6 ins., loosely set, dimly mkd. 1/4 on west face, and in a mound of stone, 3 ft. base. (Record; no marks visible on granite sandstone and no mound of stone.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

T28S R3W
1/4
S20 | S21
1999

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
39.985	<p>Bury mkd. stone on west side of aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a sagebrush flat.</p> <hr/> <p>N. 0°34.6' W., beginning new measurement.</p> <p>The cor. of secs. 16, 17, 20 and 21, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, with an aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located on a rolling east slope in sagebrush.</p> <hr/>
20.755	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 88°46.1' W., bet. secs. 16 and 21</p> <p>Point for the E 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 6 ins. in the ground to solid rock with a magnet at base, and in a supporting mound of stone, 6 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>S16</p> <p>E 1/16 —————</p> <p>S21</p> <p>1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on an east slope in scattered sagebrush, and 380 lks. West of a dirt road, 14 ft. wide, bears NE and SW.</p>
41.510	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with a white sandstone, 12X10X10 ins., loosely set, dimly mkd. 1/4 on north face, with a reference mound of stone to the south.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., with aluminum cap mkd.:</p>


SURVEY OF THE SUBDIVISION OF SECTION 3,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

CHAINS	<div style="text-align: center;"> <p>T28S R3W S16 1/4 ————— S21 1999</p> </div> <p>Bury mkd. stone along east side of aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a south slope in a ravine and sagebrush.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°56.4' W., beginning new measurement.</p> <p>40.397 The cor. of secs. 16, 17, 20 and 21.</p> <hr/> <div style="text-align: center;"> <p>Survey of the Subdivision of Section 3 T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> </div> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0°31.3' W., on the N-S center line of sec. 3.</p> <p>20.308 Point for the center S 1/16 sec. cor. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>C S 1/16 S3 C 1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a steep south slope in shad scale and grass, and 15 lks. North of a ridge, bears NE and SW.</p> <p>30.462 Point for the center – S 1/64 sec. cor. of sec. 3. Not monumented.</p> <p>40.616 Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E-W center line.</p>
--------	--


SURVEY OF THE SUBDIVISION OF SECTION 3
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">T28S R3W C 1/4 S3 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a northwest slope in sagebrush and grass, and 53 lks. West of a spur ridge, bears NE and SW.</p>
80.149	<p>The 1/4 sec. cor. of secs. 3 and 34, on the north bdy. of the tp., hereinbefore described.</p>
	<hr/> <p>From the 1/4 sec. cor. of sec. 3 only, on the east bdy. of section 3.</p> <p>S. 89°04.6' W., on the E-W center line of sec. 3.</p>
41.130	<p>The center 1/4 sec. cor. of sec. 3.</p>
51.192	<p>Point for the center E-W 1/64 sec. cor. of sec. 3. Not monumented.</p>
61.254	<p>Point for the center W 1/16 sec. cor. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">W 1/16 C ——— C S3 1999</p>
	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located in a pasture on flat ground, and 12 lks. North of a fence, bears E and W.</p>
81.378	<p>The 1/4 sec. cor. of secs. 3 and 4.</p>

SURVEY OF THE SUBDIVISION OF SECTION 3
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Cor. is located on a flat, in grass and sagebrush, and in a fence, bears E and W.</p> <hr/> <p>From the point for the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°23.9' W., on the N-S center line of the SW 1/4 of sec. 3.</p>
20.379	<p>Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E-W center line of the SW 1/4 of sec. 3. Not monumented.</p>
28.020	<p>Point for the 1/1024 sec. cor. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <div style="text-align: center;">  <p>1999</p> </div> <p>Drive a steel fence post along south side of aluminum post.</p> <p>Cor. is located in sand and rabbit brush, and 100 lks. North of the present north bank of the Sevier River, drains SW.</p>
30.567	<p>Point for the center N-SW 1/64 sec. cor. of sec. 3. Not monumented.</p>
40.755	<p>The center W 1/16 sec. cor. of sec. 3.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 3.</p> <p>S. 88°52.6' W., on the E-W center line of the SW 1/4 of sec. 3.</p>
10.084	<p>Point for the center E-SW 1/64 sec. cor. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>C-E-SW 1/64</p> <p>S3</p> <p>1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p>

SURVEY OF THE SUBDIVISION OF SECTION 3,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	Cor. is located on a flat in shad scale, and 150 lks. West of the Sevier River, 66 ft. wide, flows NE.
20.168	Point for the SW 1/16 sec. cor. of sec. 3.
40.337	Point for the S 1/16 sec. cor. of secs. 3 and 4.
7.629	<p>From the center E-SW 1/64 sec. cor. of sec. 3.</p> <p>N. 0°27.6' W., on the N-S center line of the NE 1/4 of the SW 1/4 of sec. 3.</p> <p>Point for the 1/1024 sec. cor. of sec. 3.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <div style="text-align: center;">  <p>1024</p> <p>1999</p> </div> <p>Drive a steel fence post along south side of aluminum post.</p> <p>Cor. is located on a flat in rabbit brush.</p>
10.172	Point for the NE-SW 1/64 sec. cor. of sec. 3, at intersection with the E-W center line of the NE 1/4 of the SW 1/4 of sec. 3. Not monumented.
20.344	Point for the center E-W 1/64 sec. cor. of sec. 3.
10.073	<p>From the point for the center N-S 1/64 sec. cor. of sec. 3.</p> <p>S. 88°58.6' W., on the E-W center line of the NE 1/4 of the SW 1/4 of sec. 3.</p> <p>Point for the NE-SW 1/64 sec. cor. of sec. 3.</p>
20.146	Point for the center N-SW 1/64 sec. cor. of sec. 3.

SURVEY OF THE SUBDIVISION OF SECTION 3,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>From the 1/1024 sec. cor. on the N-S center line of the NE 1/4 of the SW 14 of sec. 3.</p> <p>S. 88°57.1' W., on the E-W center line of the N 1/2 of the SW 1/4 of the NE 1/4 of the SW 1/4 of sec. 3.</p>
10.076	<p>The 1/1024 sec. cor. on the N-S center line of the SW 1/4 of sec. 3..</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 3.</p> <p>N. 0°30.5' W., on the N-S center line of the NW 1/4 of sec. 3.</p>
39.689	<p>The W 1/16 sec. cor. of secs, 3 and 34, on the north bdy. of the tp., hereinbefore described.</p> <hr/> <p style="text-align: center;">Survey of the Subdivision of Section 10, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 1°26.3' W., on the N-S center line of sec. 10.</p>
39.749	<p>Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E-W center line of sec. 10.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">T28S R3W C 1/4 S10 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on flat ground in a pasture and 100 lks. West of a fence, bears N and S.</p>
59.780	<p>Point for the center N 1/16 sec. cor. of sec. 10.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">C N 1/16 S10 C 1999</p>

SURVEY OF THE SUBDIVISION OF SECTION 10
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	Drive a steel fence post alongside aluminum post.
	Cor. is located on a flat in pasture
79.811	The 1/4 sec. cor. of secs. 3 and 10.
19.810	<p>From the 1/4 sec. cor. of sec. 10 only, on the east bdy. of sec. 10.</p> <p>S. 88°44.1' W., on the E-W center line of sec. 10.</p> <p>Point for the center E 1/16 sec. cor. of sec. 10.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 1/2 ft. diam., with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>E 1/16</p> <p>C — C</p> <p>S10</p> <p>1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a SW slope, 18 lks. North of a fence, bear E and W.</p>
39.620	The center 1/4 sec. cor. of sec. 10.
80.156	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd. and witnessed as described in the field notes of the 1989 resurvey record.</p> <p>Cor. is located on a gradual east slope in sagebrush, 76 lks. East of a netwire fence, bears N and S, and 30 lks. North of a fence, bears E and W.</p>
20.095	<p>From the center E 1/16 sec. cor. of sec. 10.</p> <p>N. 0°51.3' W., on the N-S center line of the NE 1/4 of sec. 10.</p> <p>Point for the NE 1/16 sec. cor. of sec.10, at intersection with the E-W center line of the NE 1/4 of sec. 10.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p>

SURVEY OF THE SUBDIVISION OF SECTION 10,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	<div style="text-align: center; margin-bottom: 10px;">NE 1/16 S10 1999</div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southeast slope, 23 lks. East of a draw, drains SW.</p> <p>40.189 The E 1/16 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the N 1/16 sec. cor. of sec. 10 only, on the east bdy. of sec.10.</p> <p>S. 88°33.2' W., on the E-W center line of the NE 1/4 of sec. 10.</p> <p>20.013 The NE 1/16 sec. cor. of sec. 10.</p> <p>40.026 The center N 1/16 sec. cor. of sec. 10.</p> <hr/> <div style="text-align: center; margin-bottom: 10px;">Survey of the Subdivision of Section 15, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</div> <hr/> <p>From the 1/4 sec. cor. of secs. 15 and 22.</p> <p>N. 1°48.7' W., on the N-S center line of sec. 15.</p> <p>20.093 Point for the center S 1/16 sec. cor. of sec. 15.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center; margin: 10px 0;"> C S 1/16 S15 C 1999 </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a gradual north slope in sagebrush and rabbit brush.</p> <p>40.186 Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E-W center line of sec. 15.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p>
---------------	---

SURVEY OF THE SUBDIVISION OF SECTION 15,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p style="text-align: center;">T28S R3W C 1/4 S15 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a steep southerly slope in sagebrush and grass.</p>
60.274	<p>Point for the center N 1/16 sec. cor. of sec. 15.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">C N 1/16 S15 C 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a slight northwest slope, in sagebrush.</p>
80.362	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/>
	<p>From the 1/4 sec. cor. of sec. 15 only, on the east bdy. of sec. 15.</p> <p>S. 88°33.5' W., on the E-W center line of sec. 15.</p>
39.571	<p>The center 1/4 sec. cor. of sec. 15.</p>
60.054	<p>Point for the center W 1/16 sec. cor. of sec. 15.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">W 1/16 C — C S15 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a flat in sagebrush, 50 lks. West of the base of a rock cliff.</p>

SURVEY OF THE SUBDIVISION OF SECTION 15,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
80.537	Point for the 1/4 sec. cor. of secs. 15 and 16.
	<hr/> <p data-bbox="430 527 1047 555">From the point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p data-bbox="430 589 1089 617">N. 1°34.9' W., on the N-S center line of the SW 1/4 of sec. 15.</p>
20.051	True point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the SW 1/4 of sec. 15, falls on a rock cliff where it is impractical to monument.
40.102	The center W 1/16 sec. cor. of sec. 15.
	<hr/> <p data-bbox="430 859 881 887">From the center S 1/16 sec. cor. of sec. 15.</p> <p data-bbox="430 921 1105 949">S. 88°40.6' W., on the E-W center line of the SW 1/4 of sec. 15.</p>
20.564	True point for the SW 1/16 sec. cor. of sec. 15.
20.700	Point selected for the witness SW 1/16 sec. cor. of sec. 15.
	<p data-bbox="430 1123 1406 1185">Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with aluminum cap mkd.:</p> <p data-bbox="786 1251 831 1278" style="text-align: center;">WC</p> <p data-bbox="740 1312 941 1340" style="text-align: center;">SW1/16 S15 →</p> <p data-bbox="782 1376 834 1404" style="text-align: center;">1999</p> <p data-bbox="430 1440 954 1468">Drive a steel fence post alongside aluminum post.</p> <p data-bbox="430 1504 1425 1566">Cor. is located on a westerly slope at the base of a rock cliff, 38 lks. South of the east end of a fence, bears West.</p>
41.129	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	<hr/> <p data-bbox="430 1704 891 1732">From the center W 1/16 sec. cor. of sec. 15.</p> <p data-bbox="430 1766 1094 1793">N. 1°34.9' W., on the N-S center line of the NW 1/4 of sec. 15.</p>

SURVEY OF THE SUBDIVISION OF SECTION 15,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
20.049	<p>Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E-W center line of the NW 1/4 of sec. 15, falls in a wet swamp area.</p> <p>Set a steel fence post, 66 ins. long, 60 ins. in the ground, and place an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground to bedrock, with a magnet at base, over steel fence post, and in a collar of stone, 1 1/2 ft. diam., with aluminum cap mkd.:</p>
	<p style="text-align: center;">NW 1/16 S15 1999</p>
	<p>Drive a steel fence post 2 lks. West of aluminum post.</p>
	<p>Cor. is located in a swamp area.</p>
40.097	<p>The W 1/16 sec. cor. of secs. 10 and 15.</p>
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 15.</p>
	<p>S. 88°26.9' W., on the E-W center line of the NW 1/4 of sec. 15.</p>
20.400	<p>The NW 1/16 sec. cor. of sec. 15.</p>
40.801	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16.</p>
	<hr/> <p style="text-align: center;">Survey of the Subdivision of Section 21, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p>
	<p>N. 0°34.7' W., on the N-S center line of sec. 21.</p>
19.636	<p>Point for the center S 1/16 sec. cor. of sec. 21.</p>
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:</p>
	<p style="text-align: center;">C S 1/16 S21 C 1999</p>

SURVEY OF THE SUBDIVISION OF SECTION 21,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
39.272	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a sagebrush flat, 23 lks. West to a dirt road, 8 ft. wide, bears SE and NW.</p> <p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E-W center line of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">T28S R3W C 1/4 S21 1999</p>
59.231	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located in a gravel pit.</p> <p>Point for the center N 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">C N 1/16 S21 C 1999</p>
79.190	<p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southeast slope in sagebrush.</p> <p>The 1/4 sec. cor. of secs. 16 and 21.</p>
19.886	<hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 88°50.8' W., on the E-W center line of sec. 21.</p> <p>The center E 1/16 sec. cor. of sec. 21, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p>

SURVEY OF THE SUBDIVISION OF SECTION 21,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">E 1/16 C — C S21 1999</p> <p>Bury rebar inside aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located in sagebrush, on a spur ridge, slopes NE.</p> <hr/> <p>S. 88°50.8' W., beginning new measurement.</p>
19.886	The center 1/4 sec. cor. of sec. 21.
40.087	<p>Point for the center W 1/16 sec. cor. of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, with aluminum cap mkd.:</p> <p style="text-align: center;">W 1/16 C — C S21 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southeast slope in sagebrush.</p>
60.288	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 21.</p> <p>N. 0°40.2' E., on the N-S center line of the NE 1/4 of sec. 21.</p>
19.982	<p>Point for the NE 1/16 sec. cor. of sec. 21, at intersection with the E-W center line of the NE 1/4 of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p>

SURVEY OF THE SUBDIVISION OF SECTION 21,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	<div data-bbox="740 425 881 485" data-label="Section-Header"> <p style="text-align: center;">NE 1/16 S21 1999</p> </div> <div data-bbox="428 519 959 549" data-label="Text"> <p>Drive a steel fence post alongside aluminum post.</p> </div> <div data-bbox="428 583 997 612" data-label="Text"> <p>Cor. is located 100 lks. North of a wash, drains ENE.</p> </div> <div data-bbox="428 646 1414 740" data-label="Text"> <p>From this cor., an unrecorded rebar, 3/8 in. diam., firmly set, projecting 2 ins. above ground, with a steel fence post alongside, bears S. 86°33.9' W., 0.224 chs. dist., set using incorrect procedures, and is not utilized during the course of this resurvey.</p> </div> <div data-bbox="224 774 315 804" data-label="Text"> <p>39.964</p> </div> <div data-bbox="428 774 846 804" data-label="Text"> <p>The E 1/16 sec. cor. of secs. 16 and 21.</p> <hr/> </div> <div data-bbox="428 876 906 906" data-label="Text"> <p>From the N 1/16 sec. cor. of secs. 21 and 22.</p> </div> <div data-bbox="428 940 1105 970" data-label="Text"> <p>S. 88°48.4' W., on the E-W center line of the NE 1/4 of sec. 21.</p> </div> <div data-bbox="224 1004 315 1034" data-label="Text"> <p>20.320</p> </div> <div data-bbox="428 1004 776 1034" data-label="Text"> <p>The NE 1/16 sec. cor. of sec. 21.</p> </div> <div data-bbox="224 1068 315 1098" data-label="Text"> <p>40.640</p> </div> <div data-bbox="428 1068 829 1098" data-label="Text"> <p>The center N 1/16 sec. cor. of sec. 21.</p> <hr/> </div> <div data-bbox="428 1174 902 1204" data-label="Text"> <p>From the E 1/16 sec. cor. of secs. 21 and 28.</p> </div> <div data-bbox="428 1238 1084 1268" data-label="Text"> <p>N. 0°39.1' W., on the N-S center line of the SE 1/4 of sec. 21.</p> </div> <div data-bbox="224 1302 315 1332" data-label="Text"> <p>19.923</p> </div> <div data-bbox="428 1302 1414 1395" data-label="Text"> <p>The SE 1/16 sec. cor. of sec. 21, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a faithful and careful determination of the position of the cor.</p> </div> <div data-bbox="428 1430 607 1459" data-label="Text"> <p>At the cor. point</p> </div> <div data-bbox="428 1493 1409 1557" data-label="Text"> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:</p> </div> <div data-bbox="740 1591 881 1651" data-label="Section-Header"> <p style="text-align: center;">SE 1/16 S21 1999</p> </div> <div data-bbox="428 1685 786 1715" data-label="Text"> <p>Bury rebar inside aluminum post.</p> </div> <div data-bbox="428 1749 959 1779" data-label="Text"> <p>Drive a steel fence post alongside aluminum post.</p> </div>
---------------	---

SURVEY OF THE SUBDIVISION OF SECTION 21,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	<p>Cor. is located on a slight east slope in sagebrush and 30 lks. West of a draw, 4 lks. wide, drains NE.</p> <hr/>
19.917	<p>N. 0°41.0' W., beginning new measurement.</p> <p>The center E 1/16 sec. cor. of secs. 16 and 21.</p> <hr/>
19.911	<p>From the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>S. 89°40.3' W., on the E-W center line of the SE 1/4 of sec. 21.</p> <p>The SE 1/16 sec. cor. of sec. 21.</p> <hr/>
19.922	<p>S. 89°39.4' W., beginning new measurement.</p> <p>The center S 1/16 sec. cor. of sec. 21.</p> <hr/>
19.827	<p>From the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>N. 0°30.0' W., on the N-S center line of the SW 1/4 of sec. 21.</p> <p>Point for the SW 1/16 sec. cor. of sec. 21, at intersection with the E-W center line of the SW 1/4 of sec. 21.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">SW 1/16 S21 1999</p> <p>Drive a steel fence post alongside aluminum post.</p>
39.654	<p>Cor. is located on a slight east slope in sagebrush, and 15 lks. South of a draw, 8 lks. wide, drains easterly.</p> <p>The center W 1/16 sec. cor. of sec. 21.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 21.</p> <p>S. 88°18.4' W., on the E-W center line of the SW 1/4 of sec. 21.</p>

SURVEY OF THE SUBDIVISION OF SECTION 22,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	
20.232	The SW 1/16 sec. cor. of sec. 21.
40.464	The S 1/16 sec. cor. of secs. 20 and 21.
	<hr/> Survey of the Subdivision of Section 22, T. 28 S., R. 3 W., Salt Lake Meridian, Utah <hr/>
	From the 1/4 sec. cor. of secs. 22 and 27.
	N. 0°51.4' E., on the N-S center line of sec. 22.
40.663	Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E-W center line of sec. 22, falls on the west bank of the Sevier River, below the high water mark, where it is impractical to monument. Not monumented.
60.882	Point for the center N 1/16 sec. cor. of sec. 22. Not monumented.
81.101	The 1/4 sec. cor. of secs. 15 and 22.
	From the 1/4 sec. cor. of sec. 22 only, on the east bdy. of sec. 22.
	S. 89°23.4' W., on the E-W center line of sec. 22.
19.828	Point for the center E 1/16 sec. cor. of sec. 22. Not monumented.
39.656	Point for the center 1/4 sec. cor. of sec. 22.
60.668	Point for the center W 1/16 sec. cor. of sec. 22.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:
	W 1/16 C ——— C S22 1999
	Drive a steel fence post alongside aluminum post.
	Cor. is locate on a gradual easterly slope in sagebrush.

SURVEY OF THE SUBDIVISION OF SECTION 22,
T.28S., R.3W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	<p>From this point, an unrecorded rebar, 3/8 in. diam., firmly set, projecting 2 ins. above ground, bears S. 86°27.1'W., 0.459 chs. dist., set using incorrect procedures and is not utilized during the course of this resurvey.</p>
81.680	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/>
20.321	<p>From the point for the center E 1/16 sec. cor. of sec. 22.</p> <p>N. 0°01.9' E., on the N-S center line of the NE 1/4 of sec. 22.</p> <p>Point for the NE 1/16 sec. cor. of sec. 22, at intersection with the E-W center line of the NE 1/4 of sec. 22.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">NE 1/16 S22 1999</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southwesterly slope in rabbit brush.</p>
40.642	<p>The E 1/16 sec. cor. of secs. 15 and 22.</p> <hr/>
19.537	<p>From the N 1/16 sec. cor. of sec. 22 only, on the east bdy. of sec. 22.</p>
39.073	<p>S. 89°04.7' W., on the E-W center line of the NE 1/4 of sec. 22.</p> <p>The NE 1/16 sec. cor. of sec. 22.</p> <p>Point for the center N 1/16 sec. cor. of sec. 22.</p> <hr/>
40.532	<p>From the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 0°03.2' E., on the N-S center line of the SW 1/4 of sec. 22.</p> <p>The center W 1/16 sec. cor. of sec. 22.</p> <hr/>

SURVEY OF THE SUBDIVISION OF SECTION 25,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p style="text-align: center;">Survey of the Subdivision of Section 25, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> <hr/>
39.852	<p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°05.6' W., on the N-S center line of sec. 25.</p> <p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line of sec. 25.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">T28S R3W C 1/4 S25 1999</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in scattered sagebrush.</p>
80.088	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/>
20.104	<p>From the 1/4 sec. cor. of secs. 25 and 29, on the east bdy. of the tp., hereinbefore described.</p> <p>S. 89°26.1' W., on the E-W center line of sec. 25.</p> <p>Point for the center E 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">E 1/16 C — C S25 1999</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in sagebrush, and 50 lks. West of the easterly edge of the flat.</p>
40.208	<p>The center 1/4 sec. cor. of sec. 25.</p>

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 28 S., R. 3 W., SALT MERIDIAN, UTAH

<i>CHAINS</i>	
80.192	The 1/4 sec. cor. of secs. 25 and 26.
	From the E 1/16 sec. cor. of secs. 25 and 36.
	N. 0°04.8' E., on the N-S center line of the SE 1/4 of sec. 25.
40.000	The center E 1/16 sec. cor. of sec. 25.
	Survey of the Subdivision of Section 27, T. 28 S., R. 3 W., Salt Lake Meridian, Utah
	From the 1/4 sec. cor. of secs. 27 and 34.
	N. 0°40.8' W., on the N-S center line of sec. 27.
19.737	The center S 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as a careful and faithful determination of the position of the cor.
	At the cor. point
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:
	$\begin{array}{c} C \\ S\ 1/16 \mid S27 \\ C \\ 1999 \end{array}$
	Bury rebar inside aluminum post.
	Drive a steel fence post alongside aluminum post.
	Cor. is located on a steep northerly slope in sagebrush.
	N. 0°42.6' W., beginning new measurement.
19.742	Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W center line of sec. 27.
	Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 28 S., R. 3 W., SALT MERIDIAN, UTAH

CHAINS	
39.508	<div style="text-align: center;"> <p>T28S R3W C 1/4 S27 1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a northerly slope in sagebrush and 70 lks. South of a draw, drains NE.</p> <p>The center N 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 4 ins. above ground, and is accepted as a faithful and careful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>C N 1/16 S27 C 1999</p> </div> <p>Bury rebar inside aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a gradual northerly slope in grass and scattered sagebrush, 45 lks. South of a draw, drains NE, and 23 lks. South of same draw.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°42.2' W., beginning new measurement.</p>
19.769	<p>The 1/4 sec. cor. of secs 22 and 27.</p> <hr style="width: 60%; margin: 10px auto;"/>
20.485	<p>From the 1/4 sec. cor. of sec 27 only, on the east bdy. of sec. 27.</p> <p>S. 88°29.5' W., on the E-W center line of sec. 27.</p> <p>The center E 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 1 in. above ground, and is accepted as a faithful and careful determination of the position of the cor.</p> <p>At the cor. point</p>

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 28 S., R. 3 W., SALT MERIDIAN, UTAH

CHAINS

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:

E 1/16
C ——— C
S27
1999

Bury the rebar inside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a westerly slope, 10 lks. East of a draw, drains NW.

S. 88°30.7'W., beginning new measurement.

20.501

The center 1/4 sec. cor. of sec. 27.

61.424

The 1/4 sec. cor. of secs. 27 and 28.

From the center E 1/16 sec. cor. of sec. 27.

N. 0°48.2' W., on the N-S center line of the NE 1/4 of sec. 27.

19.541

The NE 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 2 ins. above ground, and is accepted as a faithful and careful determination of the position of the cor.

At the cor. point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 2 ft. diam., with aluminum cap mkd.:

NE 1/16 S 27
1999

Bury rebar inside aluminum post.

Drive a steel fence post alongside aluminum post.

Cor. is located on a flat in sagebrush, 15 lks. West of a fence, bears SE and NW.

SURVEY OF THE SUBDIVISION OF SECTION 27,
T. 28 S., R. 3 W., SALT MERIDIAN, UTAH

CHAINS	
19.559	<p>N. 0°46.1' W., beginning new measurement.</p> <p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <hr/>
20.469	<p>From the point for the N 1/16 sec. cor. of sec. 27 only, on the east bdy. of sec. 27.</p> <p>S. 89°05.0' W., on the E-W center line of the NE 1/4 of sec. 27.</p> <p>The NE 1/16 sec. cor. of sec. 27.</p> <hr/>
20.466	<p>S. 89°08.4' W., beginning new measurement.</p> <p>The center N 1/16 sec. cor. of sec. 27.</p> <hr/>
19.527	<p>From the E 1/16 sec. cor. of secs. 27 and 34.</p> <p>N. 0°45.5' W., on the N-S center line of the SE 1/4 of sec. 27.</p> <p>The SE 1/16 sec. cor. of sec. 27, monumented with an unrecorded rebar, 3/8 in. diam., firmly set, projecting 1 in above ground, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <p style="text-align: center;">SE 1/16 S 27 1999</p> <p>Bury rebar inside aluminum post.</p> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a southerly slope in scattered rabbit brush, and 125 lks. North of the base of a ridge.</p> <hr/>

SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

<i>CHAINS</i>	<div data-bbox="430 421 899 453" data-label="Text"> <p>N. 0°45.5' W., beginning new measurement.</p> </div> <div data-bbox="224 485 313 517" data-label="Text"> <p>19.538</p> </div> <div data-bbox="430 491 829 523" data-label="Text"> <p>The center E 1/16 sec. cor. of sec. 27.</p> <hr/> </div> <div data-bbox="430 591 1154 623" data-label="Text"> <p>From the S 1/16 sec. cor. of sec. 27 only, on the east bdy. of sec. 27.</p> </div> <div data-bbox="430 655 1099 687" data-label="Text"> <p>S. 87°54.6' W., on the E-W center line of the SE 1/4 of sec. 27.</p> </div> <div data-bbox="224 719 313 751" data-label="Text"> <p>20.520</p> </div> <div data-bbox="430 723 773 755" data-label="Text"> <p>The SE 1/16 sec. cor. of sec. 27.</p> <hr/> </div> <div data-bbox="430 823 907 855" data-label="Text"> <p>S. 87°56.5' W., beginning new measurement.</p> </div> <div data-bbox="224 887 313 919" data-label="Text"> <p>20.522</p> </div> <div data-bbox="430 891 829 923" data-label="Text"> <p>The center S 1/16 sec. cor. of sec. 27.</p> <hr/> </div> <div data-bbox="568 989 1042 1051" data-label="Section-Header"> <p style="text-align: center;">Survey of the Subdivision of Section 34, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> <hr/> </div> <div data-bbox="430 1119 1406 1151" data-label="Text"> <p>From the 1/4 sec. cor. of secs. 3 and 34, on the south bdy. of the tp., hereinbefore described.</p> </div> <div data-bbox="430 1183 928 1215" data-label="Text"> <p>N. 0°40.9' E., on the N-S center line of sec. 34.</p> </div> <div data-bbox="224 1247 313 1278" data-label="Text"> <p>39.445</p> </div> <div data-bbox="430 1251 1421 1312" data-label="Text"> <p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E-W center line of section 34.</p> </div> <div data-bbox="430 1347 1409 1438" data-label="Text"> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, with a magnet at base, and in a supporting mound of stone, 3 ft. diam., to top, with brass cap mkd.:</p> </div> <div data-bbox="738 1472 870 1564" data-label="Text"> <p style="text-align: center;">T28S R3W C 1/4 S34 1999</p> </div> <div data-bbox="430 1600 995 1632" data-label="Text"> <p>Drive a steel fence post alongside stainless steel post.</p> </div> <div data-bbox="430 1664 1023 1696" data-label="Text"> <p>Cor. is located on a gradual east slope in boulder (rock).</p> </div> <div data-bbox="224 1727 313 1759" data-label="Text"> <p>80.078</p> </div> <div data-bbox="430 1732 812 1764" data-label="Text"> <p>The 1/4 sec. cor. of secs. 27 and 34.</p> <hr/> </div> <div data-bbox="430 1832 1118 1864" data-label="Text"> <p>From the 1/4 sec. cor. of sec. 34 only, on the east bdy. of sec. 34.</p> </div>
---------------	---

SURVEY OF THE SUBDIVISION OF SECTION 34,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

*CHAINS***20.365**

S. 88°02.1' W., on the E-W center line of sec. 34.

Point for the center E 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 4 ft. diam., to top, with brass cap mkd.:

E 1/16
C — C
S34
1999

Drive a steel fence post alongside stainless steel post.

from which

A BXO, 5 1/2 ft. above base of rock, 50 ft. high, bears S. 82° E., 5.3 lks. dist.

Cor. is located on a steep westerly slope in sagebrush and 6 lks. West of the base of a vertical rock cliff.

From this cor. an unrecorded rebar, 1/2 in. diam., firmly set, projecting 2 ins. above ground, with a steel fence post alongside, bears S. 71°05.5' E., 1.047 chs. dist., set using incorrect procedures and is not utilized during the course of this resurvey.

40.730

The center 1/4 sec. cor. of sec. 34.

60.829

Point for the center W 1/16 sec. cor. of sec. 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground to bedrock, with a magnet at base, and in a supporting mound of stone, 5 ft. diam., to top, with brass cap mkd.:

W 1/16
C — C
S34
1999

Drive a steel fence post alongside stainless steel post.

Cor. is located on a steep southerly slope, 8 lks. North of the south edge of a small rock ledge, and 80 lks. North of a wash, 8 lks. wide, drains NE.

80.928

The 1/4 sec. cor. of secs. 33 and 34.

SURVEY OF THE SUBDIVISION OF SECTION 36,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
40.884	<p>From the center E 1/16 sec. cor. of sec. 34.</p> <p>N. 0°56.0' E., on the N-S center line of the NE 1/4 of sec. 34.</p> <p>The E 1/16 sec. cor. of secs. 27 and 34.</p>
40.290	<p>From the E 1/16 sec. cor. of secs. 3 and 34, on the south bdy. of the tp., hereinbefore described</p> <p>N. 0°56.2' E., on the N-S center line of the SE 1/4 of sec. 34.</p> <p>The center E 1/16 sec. cor. of sec. 34.</p>
38.613	<p>From the W 1/16 sec. cor. of secs. 3 and 34, on the south bdy. of the tp., hereinbefore described.</p> <p>N. 0°48.5' E., on the N-S center line of the SW 1/4 of sec. 34.</p> <p>The center W 1/16 sec. cor. of sec. 34.</p>
20.039	<p style="text-align: center;">Survey of the Subdivision of Section 36, T. 28 S., R. 3 W., Salt Lake Meridian, Utah</p> <p>From the 1/4 sec. cor. of secs. 1 and 36, on the south bdy. of the tp., hereinbefore described.</p> <p>N. 0°02.8' W., on the N-S center line of sec. 36.</p> <p>Point for the center S 1/16 sec. cor. of sec. 36.</p> <p>Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 3 ft. diam., to top, with aluminum cap mkd.:</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S36</p> <p>C</p> <p>1999</p> </div> <p>Drive a steel fence post alongside aluminum post.</p> <p>Cor. is located on a flat in sagebrush.</p>

SURVEY OF THE SUBDIVISION OF SECTION 36,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
40.078	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E-W center line of sec. 36.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 1/2 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">T28S R3W C 1/4 S36 1999</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a gradual easterly slope in sagebrush.</p>
60.104	<p>Point for the center N 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., with brass cap mkd.:</p> <p style="text-align: center;">C N 1/16 S36 C 1999</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in sagebrush.</p>
80.130	<p>The 1/4 sec. cor. of secs. 25 and 36.</p>
20.009	<hr/> <p>From the 1/4 sec. cor. of secs. 32 and 36, on the east bdy. of the tp., hereinbefore described.</p> <p>S. 89°55.7' W., on the E-W center line of sec. 36.</p> <p>Point for the center E 1/16 sec. cor. of sec. 36.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, with a magnet at base, and in a mound of stone, 2 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">E 1/16 C — C S36 1999</p>

SURVEY OF THE SUBDIVISION OF SECTION 36,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS	
	<p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in sagebrush.</p>
40.018	The center 1/4 sec. cor. of sec. 36.
80.063	The 1/4 sec. cor. of secs. 35 and 36.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 36.</p> <p>N. 0°04.6' W., on the N-S center line of the NE 1/4 of sec. 36.</p>
20.038	<p>Point for the NE 1/16 sec. cor. of sec. 36, at intersection with the E-W centerline of the NE 1/4 of sec. 36.</p> <p>Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground to bedrock, with a magnet at base, and in a collar of stone, 1 ft. diam., to top, with brass cap mkd.:</p> <p style="text-align: center;">NE 1/16 S36 1999</p> <p>Drive a steel fence post alongside stainless steel post.</p> <p>Cor. is located on a flat in sagebrush.</p>
40.076	The E 1/16 sec. cor. of secs. 25 and 36.
	<hr/> <p>From the point for the N 1/16 sec. cor. of secs. 32 and 36, on the east bdy. of sec. 36, hereinbefore described..</p> <p>S. 89°53.6' W., on the E-W center line of the NE 1/4 of sec. 36.</p>
19.997	The NE 1/16 sec. cor. of sec. 36.
39.994	The center N 1/16 sec. cor. of sec. 36.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 36.</p> <p>S. 89°54.5' W., on the E-W center line of the SW 1/4 of sec. 36.</p>

SURVEY OF THE SUBDIVISION OF SECTION 36,
T. 28 S., R. 3 W., SALT LAKE MERIDIAN, UTAH

CHAINS

40.039

The S 1/16 sec. cor. of secs. 35 and 36.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Burke Williams	Resource Specialist
Max L Sevy	Volunteer (retired supervisory cadastral surveyor)
Kevin McKee	Survey Aid
Greg Evans	Realty Technician

CERTIFICATE OF SURVEY

I, *John F. Carroll, Cadastral Surveyor*, **HEREBY CERTIFY** upon honor that, in pursuance of Special Instructions bearing the date of the 8th day of January, 1999, I have *dependently resurveyed a portion of the north, south and east boundaries, a portion of the subdivisional lines and the survey of the subdivision of sections 3, 10, 15, 21, 22, 25, 27, 34 and 36, in Township 28 South, Range 3 West,*

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said Special Instructions, the Manual of Instructions for the survey of the Public Lands of the United States, and is specific manner described in the foregoing field notes.

1-19-2001

Date

John F. Carroll

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the north, south and east boundaries, a portion of the subdivisional lines and the survey of the subdivision of sections 3, 10, 15, 21, 22, 25, 27, 34 and 36, in Township 28 South, Range 3 West, Salt Lake Meridian, Utah,*

executed by *John F. Carroll, Cadastral Surveyor*

having been critically examined and found correct, are hereby approved.

March 9, 2001

Date

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)